

IMAGE FORMING SYSTEM AND IMAGE FORMING METHOD

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to an image forming system comprising an image editing apparatus (i.e., digitizer) capable of entering a coordinate position of an original onto a tablet and predetermined information, such as editorial details, and an image forming apparatus. More particularly, the present invention relates to an image forming system and an image forming method for generating image data in which image data regarding a plurality of originals are combined.

The present application is based on Japanese Patent Application No. 2000-032115, which is incorporated herein by reference.

2. Description of the Related Art

20 With regard to use of an image forming apparatus, such as a copier, a stencil printing machine, etc., there has been recently proposed to use an image editing apparatus (i.e., digitizer) as an editing device for editing copied images. An image forming apparatus, to which a digitizer of this type is connectable, has already been commercialized.

25

5 The digitizer is equipped with a coordinate
input section for entering coordinates representing
the location of an original set on a tablet
surface, and a command input section for entering
specific editorial details. In the command input
section, there are provided various function keys
including a key to be used for indicating, for
example, the region of an editorial object within
the original, a key to be used for moving the
10 editorial object to another location, a key to be
used for indicating the movement direction and
distance over which the editorial object is to be
moved, and so on.

15 An image editing operation performed through
use of the image editing apparatus now will be
described. First, an original is set on the
tablet, and then the required positional
information and functional information are input by
use of a custom-designed pen or the like, thereby
20 acquiring positional information and functional
information.

25 Afterwards, the original is removed from the
tablet and set on an original mounting table of a
scanner. The scanner's operation is started to
read an image of the original so that the image
data is formed on the basis of editorial details
designated by the positional information and the
functional information. Based on the image data,

the image is printed on a predetermined printing sheet (e.g., printing paper).

In a case where printed matter is to be produced, using the image editing apparatus, by editing image data pertaining to a plurality of originals, an editing of images based on the plurality of originals cannot be directly performed. Therefore, only the required portion(s) of the image is extracted and edited relative to one original, and the thus-edited image is printed out. Similarly, such the process is repeatedly performed plural times relative to the remaining originals to obtain overprinted matter.

However, the above-mentioned construction of the image editing apparatus has the drawback that the number of printing operations required for producing a single sheet of printed matter is increased in proportion to the number of originals.

Another drawback of the image editing apparatus is a tendency to cause displacement of an image on the first original from an image on the n^{th} original, where "n" is 2 or more, depending on the location of a sheet.

In a case where images to be combined are printed while being changed in size, determination as to whether images are printed in appropriate positions or in appropriate sizes requires an actual printing operation, thus rendering

adjustment very difficult and involving much effort.

SUMMARY OF THE INVENTION

5 The present invention has been conceived to solve such drawbacks and is aimed at providing an image forming system and an image forming method which enable an editing of a plurality of originals in combination through a simple operation, and which enable production of printed matter that is free of displaced images.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2

on the first and second originals; and forming the composite image on a printable object in accordance with the post-editing image data. The image forming method may further comprise a step of designating an editorial process in which the image extracted area of the second original is edited relative to the image composited area of the first original, wherein the editing step is performed in accordance with the editorial process.

In the image forming method, post-editing image data can be obtained by compositing an extracted image in a first (base) original. A composite image can be printed through use of the post-editing image data by a single printing operation, whereby printed matter without displaced composite images can be obtained. Since an image to be composited is extracted and the thus-extracted image is composited into a first (base) original, useless reading of image data can be eliminated, and the volume of image data to be handled can be minimized.

According to the first aspect of the present invention, there is provided an image forming system which comprises a coordinate input device which is capable of indicating an image composited area of a first original and an image extracted area of a second original; a command input device which is capable of designating an editorial

process in which the image extracted area of the second original is edited relative to the image composited area of the first original; a scanner section which reads image data on the first and second originals; an editing device which edits image data pertaining to the image extracted area of the second original so as to composite the image extracted area of the second original into the image composited area of the first original, in accordance with the editorial process designated by the command input device, in order to obtain post-editing image data for representing a composite image based on the first and second originals; and a print device which forms the composite image on a printable object in accordance with the post-editing image data.

In the image forming system, an image, into which a plurality of images are composited, can be readily obtained by indicating only coordinates and an editorial process for each original through use of an image editing apparatus, such as a digitizer. A composite image can be printed through use of post-editing image data by a single printing operation, whereby printed matter without displaced composite images can be obtained.

According to the second aspect of the present invention, in the image forming method, it is preferable that in a case where a portion or a

whole of an image of the second original is extracted, and is composited into the first original, a size of an image composited area of the first original is compared in the editing step with a size of an image extracted area of the second original, thereby effecting a scaling process so as to fit an image located in the image extracted area to the image composited area.

Similarly, in the image forming system, it is preferable that in a case where a portion or a whole of the second original is extracted, and is composited into the first original, the editing device compares a size of an image composited area of the first original indicated by the coordinate input device with a size of an image extracted area of the second original, thereby effecting a scaling process so as to fit an image located in the image extracted area to the image composited area.

In the image forming method and system, since the size of a composited area and the size of an extracted area can be matched by the scaling operation, an extracted image can be located on and composited into the composited area on the first original. An editing of a plurality of originals can be performed readily.

According to the third aspect of the present invention, in the image forming method, it is preferable that the image extracted area of the

second original is read in accordance with a scaling factor obtained as a result of the scaling process.

Similarly, in the image forming system, it is preferable that the editing device performs a process for causing the scanner section to read the second original in accordance with a scaling factor obtained as a result of the scaling process.

In the image forming method and system, a reading of an extracted image to be extracted from an original is changed at the time of the scaling operation. According to the scaling operation to be performed during a reading operation, the quality of image data can be maintained, thereby preventing deterioration of quality of image data, which would otherwise be caused when the scaling operation is performed after reading the image.

According to the fourth aspect of the present invention, it is preferable that the image forming method further comprises a step of storing a portion or a whole of image data pertaining to the respective first and second originals, wherein a storage image obtained in the storing step is read in the editing step in order to composite a read image into the image composited area of the first original.

Similarly, it is preferable that the image forming system further comprises a storage device

which stores a portion or a whole of image data
pertaining to the respective first and second
originals read by the scanner section, wherein the
editing device reads a storage image from the
storage device, and composites a read image into
the image composited area of the first original.

In the image forming method and system, the
read image data is stored in the storage device.
Hence, a reading operation and an editorial process
can be effected separately. Accordingly, an
editorial process can be performed through use of
only the image data stored in the storage device,
thus rendering operations efficiently.

At this time, according to the fifth aspect of
the present invention, a scaling operation may be
performed such that stored image data is matched in
size with a composited area.

More specifically, according to the fifth
aspect of the present invention, it is preferable
that the image forming method further comprises a
step of storing a portion or a whole of image data
pertaining to the respective first and second
originals, wherein, in a case where a storage image
of the second original obtained in the storing step
is composited into the first original, a size of an
image composited area of the first original is
compared in the editing step with a size of an
image extracted area from which the storage image

has been extracted, thereby effecting a scaling process so as to fit an extracted storage image to the image composited area.

Similarly, it is preferable that the image forming system further comprises a storage device which stores a portion or a whole of image data pertaining to the respective first and second originals read by the scanner section, wherein, in a case where a storage image read from the storage device is composited into the first original, the editing device compares a size of an image composited area of the first original indicated by the coordinate input device with a size of an image extracted area from which the storage image has been extracted, thereby effecting a scaling process so as to fit an extracted storage image to the size of the image composited area of the first original.

By way of the construction of the image forming method and system according to the present invention, in a case where an attempt is made to produce a single printed matter by editing a plurality of originals in combination, a coordinate input device (5a) of an image editing apparatus (3) is used, thereby indicating an image composited area on a base original (40) into which another original is to be composited. Image data pertaining to the base original (40) is obtained by a scanner section (10).

An image extracted area on a second original (41) from which an image is desired to be extracted is indicated by the coordinate input device (5a), and an image to be composited is indicated by a command input device (5b).

When the second original (41) is read, the editing device (6) composites the extracted image data to the image composited area on the image data pertaining to the base original. At this time, the image composited area is compared with the image extracted area, whereby the extracted image is scaled so as to fit the image composited area. The thus-composited, post-editing image data is output to a print device (12), where the data is printed out as printed matter.

In this way, every time that an original is scanned, an extracted image is composited into the image composited area indicated on the base original.

By printing based on post-editing image data, complete printed matter can be obtained, thus providing an image without displacement.

Further, a base original, or a portion or the whole of extracted image data can be stored beforehand. An editorial process can be performed through use of the thus-stored image data.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing an embodiment of an image forming system according to the present invention;

Fig. 2 is a block diagram showing the internal construction of an editing device;

Fig. 3 is an illustration showing a first original;

Fig. 4 is an illustration showing a second original;

Fig. 5 is an illustration showing an image stored in data storage memory;

Fig. 6 is a flowchart showing details of an editorial process performed in the present invention; and

Fig. 7 is an illustration showing a printed image obtained through an editorial process.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention now will be described with reference to Figs. 1 to 7.

Fig. 1 is a block diagram showing the overall configuration of an image forming system according to the present invention. An image forming system 1 is broadly divided into an image forming apparatus 2 and an image editing apparatus 3.

The present invention will be described with reference to an example which uses a stencil-

forming/printing-type stencil printing machine as the image forming apparatus 2.

5 The image editing apparatus 3 comprises a coordinate input device 5a, a command input device 5b, and an editing device 6. Further, the image editing apparatus 3 includes a table (not shown) on which an original is to be placed. The location-coordinates on the original placed on the table are entered by the coordinate input device 5a. More specifically, the location-coordinates of the original on the table are detected, by indicating an area of the original desired to be edited, through use of a point indication pen. The editorial region can be set by indicating a plurality of points (e.g., two points or multiple points).

10 The command input device 5b is comprised of a plurality of editorial function keys provided on the side portion of the table. By pressing a desired key through use of the point indication pen, a corresponding editorial process is selected.

20 Coordinate data S1 output from the coordinate input device 5a and command data S2 output from the command input device 5b are output to the editing device 6.

25 The editing device 6 performs the editorial process designated by the command input device 5b relative to the editorial region set by the

coordinate input device 5a. Based on a plurality of originals, the editing device 6 edits the originals and composites their images. By such an editorial process, the editing device 6 outputs
5 modification data S3 to an image processing device 11 of the image forming apparatus 2. Editorial binary data S4 is input from the image processing device 11 to the editing device 6. Binary data S5, which represents print subjected to final editing, is output from the editing device 6 to the image
10 processing device 11.

The image forming apparatus 2 comprises a scanner section 10, the image processing device 11, and a print device 12. The scanner section 10 reads an original's image, and outputs image data S6 pertaining thereto. The image processing device 11 performs an editorial process set relative to the editorial region designated by the editing device 6 from among the image data S6 read by the scanner section 10, to thereby produce print image
15 data S7.

The print device 12 forms an image on a printable object, on the basis of the print image data S7.

25 Hereinafter, the embodiments of the present invention will use a printing sheet as an example of the printable object.

Here, the internal construction of the print device 12 now will be described briefly. The print device 12 is schematically comprised of a stencil-forming section and a printing section.

5 The stencil-forming section has a thermal head on which a plurality of heating elements are arranged in a line manner. On the basis of the print image data S7 output from the image processing device 11, a thermographic stencil is subjected to a stencil-forming process, whereby a
10 desired perforated image is formed of a plurality of through holes in the stencil. The printing section has a substantially-cylindrical drum which is formed from a metal screen permitting passage of ink from the interior periphery to exterior
15 periphery of the metal screen, and which is rotatable about a center line thereof, and a platen roller which rotates while pressing against the cylindrical drum. A printing sheet is fed to a
20 space between the rotating cylindrical drum and the rotating platen roller, thereby producing printed matter on which an image corresponding to the perforated image of the stencil is formed in ink.

25 Fig. 2 is a block diagram showing the interior construction of the editing device 6. The editing device 6 is roughly divided into an editorial processing device 20 and a storage device 21.

The editorial processing device 20 includes a CPU 23, an image extraction section 24, an image output section 25, and a data storage memory 26.

The storage device 21 includes a modification information memory 28, a de-archiving memory 29, and a composite memory 30.

On the basis of an execution program for editing an image stored in a storage section (not shown), the CPU 23 performs centralized control of individual sections, thus executing an image editing process (described later). The coordinate data S1 and command data S2 for editing an image are input to the CPU 23 from the coordinate input device 5a and the command input device 5b. On the basis of the thus-input data, the de-archiving modification data S10 is output to the modification information memory 28.

Editorial modification information is stored in the modification information memory 28, the modification data S3 is output to the image processing device 11, and the modification region data S12 is output to the image extraction section 24.

The editorial binary data S4 output from the image processing device 11 is input to the image extraction section 24, so that extracted data S14 pertaining to an image area extracted for an image

editorial purpose is output to the de-archiving memory 29.

The de-archiving memory 29 is a buffer for temporarily storing the extracted data S14, and the stored extracted data S14 is output to the composite memory 30 as composite data S15.

A plurality of the composite data S15 are input to the composite memory 30 by an editorial process, and stored in the composite memory 30. The thus-composited, image data is output to the image output section 25 as composited data S16.

The image output section 25 converts the composited data S16 into the binary data S5 and outputs the thus-converted binary data S5 to the image processing device 11 of the image forming apparatus 2.

Storage data S18 (identical with the composite data S15) output from the de-archiving memory 29 can be stored in the data storage memory 26. The storage data S18 is read from the data storage memory 26 in a subsequent editorial operation, and the thus-read data can be output to the composite memory 30 as memory image data S19.

Next, the image editing operation of the editing device 6 having the foregoing construction now will be described. Fig. 6 is a flowchart showing details of the editorial process.

More specifically, the image editing operation will be described with reference to an example, in which a part of an image on a second original 41 shown in Fig. 4 is extracted, the thus-extracted image is composited in (i.e., overwritten on) a predetermined area of a first original (i.e., base original) 40 shown in Fig. 3, and an image stored in the data storage memory 26 shown in Fig. 5 is composited in (i.e., superimposed on) another predetermined area of the base original 40.

The first original 40 is placed on the table of the image editing apparatus 3, the coordinates of a part of the first original 40 desired to be composited are indicated by the coordinate input device 5a (SP1), and the thus-indicated coordinates are checked (SP2). As shown in Fig. 3, an image composited area D1 and an image composited area D2 are indicated, and images (described later) are composited into the image composited areas D1 and D2. As will be described in detail later in connection with an editorial process, the original image written in the image composited area D1 is erased by overwriting, and the original image written in the image composited area D2 is erased by superimposing.

Next, the second original 41 is placed on the table of the image editing apparatus 3, and the coordinates of an area desired to be extracted on

the second original 41 (i.e., an extracted image A1) are indicated by use of the coordinate input device 5a (SP3). An editorial process, to which the image desired to be extracted is to be subjected (i.e., overwriting of the image on the image composited area D1), is determined by the command input device 5b (SP4). If there is another area desired to be extracted (YES is selected in SP5), the process proceeds to step SP3, and a similar process is iterated. If no other area is desired to be extracted (NO is selected in SP5), the extracted image A1 shown in Fig. 4 is extracted.

The command input device 5b selects memory storage image M1 stored in the data storage memory 26 shown in Fig. 5 (SP6 and SP7) and determines an editorial process to which the image data is to be subjected (i.e., overwriting of the image data onto the image composited area D2) (SP8). If there is another image desired to be extracted (YES is selected in SP9), the process proceeds to SP7, and a similar process is iterated. If no other area is desired to be extracted (NO is selected in SP9), a memory storage image M1 is read.

The first original 40 is read by the scanner section 10 (SP10), whereby multivalued data S6 is sent to the image processing device 11 from the scanner 10. The image processing device 11

converts the multivalued data S6 into editorial binary data S4 (SP11). The editorial binary data S4 is sent to the editing device 6.

The editing device 6 stores the editorial binary data S4 (SP12).

Immediately before reading a second original 41 by the scanner 10, the editing device 6 generates the region data S12 pertaining to the image composited area D1 from the coordinate data S1 pertaining to the image composited area D1. From the coordinate data S1 pertaining to the extracted image A1, the region data S12 pertaining to the extracted image A1 is generated. These two region data S12 are compared in size with each other, thereby determining a scaling factor (i.e., zooming ratio and reduction ratio) required for reading the second original 41 (SP13). The scaling factor is output to the image processing device 11 as the modification data S3.

The image processing device 11 enlarges or reduces the lateral size of image data, by changing the speed at which the scanner section 10 is to travel in a sub-scanning direction at the time of reading an original.

The longitudinal size of image data is enlarged or reduced by interpolating or thinly sampling the multivalued data S6 input to the image processing device 11 during the course of the

multivalued data S6 being converted into binary data S7.

As the second original is read by the scanner section 10 (SP14), the multivalued data S6 is input to the image processing device 11. Simultaneously, the editing device 6 inputs the modification data S3 to the image processing device 11.

At this time, the image processing device 11 performs binary-coding operation corresponding to the modification data S3 with reference thereto (SP15), and the editorial binary data S4 is output to the editing device 6.

The editing device 6 performs an image compositing operation, thereby overwriting the extracted image A1 on the image composited area D1 (SP16). These processing operations are iterated until all extracted images of the second original are composited into the first original (SP17).

After having overwriting the extracted image A1 on the image composited area D1, the editing device 6 superimposes the memory storage image M1 on the image composited area D2.

The editing device 6 determines the region data S12 pertaining to the image composited area D2 from the stored coordinate data S1 pertaining to the image composited area D2, and compares the size of the area data S12 with the size of the memory storage image M1, thus determining the scaling

factor of the memory storage image M1 (SP18). The memory storage image M1 is composited into (overwritten on) the image composited area D2 (SP19). Thus, a composite image is completed.

5 If there is no other memory storage image to be composited (NO is selected in SP20), a final composite image is completed.

10 The thus-composited image is returned to the image processing device 11 as the binary data S5 for a printing purpose. In the image processing device 11, the binary data S5 is converted into the output binary data S7, and the output binary data S7 is delivered to the print device 12.

15 Fig. 7 is an illustration showing a print image 42 produced through the compositing operations set forth. According to the foregoing operations, the extracted image A1 shown in Fig. 4 is overwritten on the image composited area D1 shown in Fig. 3, and the memory storage image M1 shown in Fig. 5 is superimposed on the image composited area D2 shown in Fig. 3.

20 The thus-edited image is printed, wherewith printed matter can be obtained. According to the construction which enables all image compositing operations at the time of an editorial process, desired printed matter without displaced images can be produced by a single printing operation.

Particularly, since the stencil printing machine is constructed to perform a stencil-forming operation on the thus-composited image data and a printing operation through use of the thus-produced stencil, only one stencil-forming operation is required. In contrast with overprinting involving use of two or more stencils, the present invention can prevent wastage of stencils.

The editorial process has been described with reference to the example involving overwriting of the extracted image A1 and superimposing of the memory storage image M1. As a matter of course, an editorial operation can be arbitrarily selected in accordance with an editorial instruction input by the command input device 5b.

A process to be performed by the editing device 6 during the editorial process will be described.

First, the coordinate data S1 pertaining to the image composited area D1 and the image composited area D2 on the first original 40 are delivered to the CPU 23 from the coordinate input device 5a and retained in the CPU 23.

Next, the coordinate data S1 pertaining to the extracted image A1 on the second original 41, and the command data S2 from the command input device 5b pertaining to the image processing operation to

which the extracted image A1 is to be subjected are delivered to and retained in the CPU 23.

Further, the command data S2 pertaining to the image processing operation to which the image composited area D2 is to be subjected is delivered to the CPU 23 from the command input device 5b and retained in the CPU 23.

Simultaneous with reading of the first original 40, the editorial binary data S4 is delivered from the image processing device 11 to the image extraction section 24. The image extraction section 24 delivers all data to the de-archiving memory 29 as the extracted data S14, and the extracted data S14 is preserved in the de-archiving memory 29.

After storage of the data into the de-archiving memory 29 has been completed, the de-archiving memory 29 sends the retained extracted data S14 to the composite memory 30 as the composite data S15. The composite data S15 is stored in the composite memory 30.

Immediately before reading of the second original 41, the CPU 23 generates the area data S12 pertaining to the image composited area D1 from the coordinate data S1 pertaining to the image composited area D1, and determines the area data S12 pertaining to the extracted image A1 from the coordinate data S1 pertaining to the extracted

image A1. The sizes of the two area data S12 are compared with each other, thereby determining a scaling factor to be used for reading the second original 41.

5 On the basis of the retained command data S2, there are determined the method of compositing the extracted image A1 relative to the image composited area D1, and the details regarding an editing of the extracted image A1.

10 The thus-determined information is delivered to and stored in the modification information memory 28 as the de-archiving modification data S10. Subsequently, simultaneous with reading of the second original 41, the modification data S3 is delivered to the image processing device 11 from the modification information memory 28, and the area data S12 is delivered to the image extraction section 24.

20 On the basis of the area data S12, the image extraction section 24 extracts image data pertaining to the extracted image A1 from the editorial binary data S4 delivered from the image processing device 11, so that extracted data S14 is formed. The thus-extracted data S14 is delivered to and stored in the de-archiving memory 29.

25 After storage of the data into the de-archiving memory 29 has been completed, the de-archiving memory 29 sends the retained data to the

composite memory 30 as the composite data S15. The composite data S15 is stored in a data portion of the image composited area D1 within the composite memory 30.

5 After the composite for the image composited area D1 has been completed, the CPU 23 determines the area data S12 pertaining to the image composited area D2 from the retained coordinate data S1 pertaining to the image composited area D2. 10 The size of the area data S12 is compared with the size of the memory storage image M1, thus determining a scaling factor of the memory storage image M1. On the basis of the retained command data S2, the method of compositing the memory storage image M1 relative to the image composited area D2, and details regarding an editing of the memory storage image M1 are determined.

 On the basis of the information determined by the CPU 23, the data storage memory 26 sends only 20 a black image of the retained memory storage image M1 to the composite memory 30 as the memory image data S19. The memory image data S19 is stored in a data portion of the image composited area 2 within the composite memory 30.

25 After storage of the data into the composite memory 30 has been completed, the composite memory 30 sends the retained data to the image output section 25 as the composited data S16. The image

output section 25 delivers the composited data S16 to the image processing device 11 as the binary data S5 for a printing purpose.

Next, a saving process for saving an image into the data storage memory 26 will be described. More specifically, the saving process will be described with reference to a case where the extracted image A2 on the second original 41 is stored.

The coordinates of the extracted image A2 on the second original 41 are indicated by the coordinate input device 5a, and the image storage process is selected by the command input device 5b, thus determining details regarding an image processing of the extracted image A2.

The coordinate data S1 and the command data S2 are delivered to the editing device 6, and are retained in the CPU 23.

Subsequently, from the data retained in the CPU 23, the CPU 23 determines the area data S12 pertaining to the image extraction section 24 and details of an image processing. The thus-determined data is delivered to and retained in the modification information memory 28 as the de-archiving modification data S10.

Afterwards, simultaneous with reading of the second original 41, the modification data S3 is delivered to the image processing device 11 from

the modification information memory 28, and the area data S12 is sent to the image extraction section 24.

Simultaneously, the multivalued data S6
5 pertaining to the second original 41 is sent to the image processing device 11 by the scanner section 10. The image processing device 11 performs a binary-coding operation, and sends the resultant editorial binary data S4 to the editing device 6.

10 On the basis of the area data S12, the image extraction section 24 extracts image data pertaining to the extracted image A2 from the binary data S4 delivered from the image processing device 11. The thus-extracted image data is sent to and stored in the de-archiving memory 29 as the extracted data S14.

After storage of the data into the de-archiving memory 29 has been completed, the data retained in the de-archiving memory 29 is sent to
20 the data storage memory 26 as the storage data S18. The storage data 18 is stored in the data storage memory 26.

Although the previous embodiment has been described with reference to an example involving
25 use of one original for image extraction and designation of only one extracted image, a plurality of originals may be used for the extraction. Further, selection of a plurality of

extracted images from a single original is also possible. For example, as shown in Fig. 4, extraction of the extracted image A2 in addition to the extracted image A1 is possible.

Further, although the present invention has been described by use of only one memory storage image, a plurality of images stored in the data storage memory 26 may be used selectively in a case where a plurality of memory storage images are stored in the data storage memory 26.

A memory serving as the storage device 21 can be constructed so as to be extendable by mounting a SIMM (i.e., Single In-line Memory Module) or like memory in the form of a socket. The memory can be freely increased or decreased in accordance with specifications of the image forming apparatus 2, such as resolution.

The storage device 21 may be constructed such that necessary data is stored into a storage medium, such as a floppy disk etc., which is detachable from an external drive unit. Of course, the storage device 21 may be equipped with such the drive unit suitable for the storage medium. In such a case, storage images can be stored in the storage medium, thereby enabling use of image data in another apparatus.

The editing device 6 of the foregoing image forming apparatus can be constructed so as to be

roughly divided into an image processing board serving as the editorial processing device 20 and a memory board serving as the storage device 21. Memory devices provided on the memory board serving as the storage device 21 are controlled by a bus controller provided in the image forming apparatus. When the image forming apparatus does not use any memory devices, the memory board may be supplied as a memory board to another apparatus.

Although the aforementioned embodiment has been described by taking the stencil printing machine as an image forming apparatus, the image editing process is not limited to the stencil printing machine. The same working-effect can be achieved even when the present invention is applied to an apparatus, such as a copier or another printing machine, which performs a predetermined editorial operation, such as a compositing operation, on the basis of a plurality of originals.